



Z H O N E

ADSL2+/ReachDSL 4 Port WiFi Modem

6388-A1-xxx

ADSL2+/ReachDSL 4 Port Switch Bridge/Router with WiFi

- ✓ *Revolutionary combination of standards based ADSL and ReachDSL on a single platform*
- ✓ *DELT - Dual Ended Loop Testing*
- ✓ *Automatically selects technology with best performance - ADSL, ADSL2, ADSL2+, or ReachDSL 2.2*
- ✓ *Speeds beyond 24 Mbps using ADSL2+*
- ✓ *Compatible with all DSLAMs providing standard ADSL, ADSL2, and ADSL2+*
- ✓ *802.11b/g Wireless Access Point*
- ✓ *Integrated telephone filter*



With Zhone's innovative, easy to use ADSL2 + /R CPE family, service providers can provide ADSL2 + service and ReachDSL service in the same unit, ensuring coverage to the entire subscriber base.

The Zhone 6300 enhanced CPE are easily user-installed. The embedded web-based user interface is designed to simplify ADSL deployment. All products provide an Ethernet connection that is auto-sensing, eliminating the worry about connection cable type (straight-through vs crossover). All units include a built in POTS filter that eliminates the expense of an external filter as well as reduces installation errors.

The 6300 enhanced CPE all default to a simple bridge. This and other default settings make for a quick and easy installation that doesn't require any configuration.

When operating in router mode, these gateways support DHCP Server/Relay/Client, NAT, as well as RIP, dynamic routing, port forwarding, static routing, and ping initiation. For security, firewall functions including PAP/CHAP and Packet Filtering are supported.

In addition, all of the CPE that make up the 6300 family support DELT, or Dual End Loop Test. Because DELT is a dual-ended test, it requires equipment that supports the DELT feature at both ends of the copper loop.

DELT is primarily used for reactive tests on a loop after a modem has been deployed—either to help troubleshoot a line or to capture a baseline of loop characteristics at the time of installation.

Technical Specifications

Dimensions

- 1.2" H x 6" W x 4.4" D (3.05cm H x 15.24cm W x 11.8cm D)

Weight

- 1.5lbs (shipping weight)

Power

- 100 VAC, 50 Hz
- 110 VAC, 60 Hz
- 220VAC, 50/60 Hz

Interfaces

- DSL Line: RJ11
- Phone: RJ11 (with integrated phone filter)
- Ethernet: 4 ports of 10/100BaseT
- WiFi: 802.11b/g

Standards Support

- ATM:
 - RFC 1483/2684 Multiprotocol Encapsulation over ATM
 - Up to 8 PVCs, UBR, CBR, VBR
 - OAM F5, F4 Loopbacks
- PPP
 - RFC 2364 PPP over ATM
 - RFC 2516 PPP over Ethernet
 - PAP/CHAP
- Routing/Bridge
 - IPv4, TCP, UDP, ICMP, ARP, RARP, proxy-ARP
 - RIPv1, RIPv2
 - Static Routing
 - DHCP Server/Client/Relay
 - DNS Proxy
 - UPNP
 - IGMP v1,v2 Snooping and Proxy
 - IEE 802.1d transparent bridging
- Security
 - NAPT
 - Stateful Inspection Firewall
 - PPP with PAP/CHAP
- Wireless
 - 802.11b/g
 - WEP, 802.1x, or WPA for wireless security
 - Supports multiple SSID's
 - Supports user isolation

Protocol Support

- ANSI T1.413 (Full Rate ADSL)
- ITU G.992.1 (DMT)
- ITU G.992.2 (G.lite)
- ITU G.992.3 (ADSL2)
- ITU G.992.5 (ADSL2+)
- ITU G.994.1 (G.hs)
- ITU G.997.1
- Zhone ReachDSL 2.2

Management

- Web based User Interface
- Firmware Upgradeable via HTTP
- Telnet Server
- TFTP Server and Client
- SNMP

Bandwidth/Distance

- Downstream Speeds up to 24 Mbps using ADSL2+ (2.2 Mbps with ReachDSL)
- Upstream speeds up to 2 Mbps with ADSL2+ (1 Mbps with ReachDSL)

Regulatory Compliance

- FCC Part 68
- FCC Part 15
- CE
- UL
- TUV
- ReachDSL 2.2 Spectral Compliance:
 - ANSI T1.417
 - ANSI T1.413
 - UK ANFP
 - ETSI TR101 830-1
 - Approved for all loops in Japan by the TTC

Operating Requirements

- Temperature: 32F to 104F (0C to 40C)
- Non-operating temperature: -4F to 149F (-20C to 65C)
- Humidity: 5% to 95%, non-condensing
- Channels 1 ~ 14
- TX Power 17dbm
- Range ~100ft
- Frequency Range ~ 2.4 - 2.5GHz

Ordering Information

| | |
|-------------|---|
| 6388-A1-200 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, N.A. |
| 6388-A1-210 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, N.A., FCC Part 68 Approved |
| 6388-A1-300 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, U.K. |
| 6388-A1-302 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, EURO |
| 6388-A1-304 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, India |
| 6388-A1-600 | ADSL2+/ReachDSL CPE Router (TI), 802.11G WiFi, Japan |



Zhone Technologies, Inc.
 @ Zhone Way
 7001 Oakport Street
 Oakland, CA 94621
 510.777.7000 phone
www.zhone.com

For more information about Zhone and its products, please visit the Zhone Web site at www.zhone.com or e-mail info@zhone.com

Zhone, the Zhone logo, and all Zhone product names are trademarks of Zhone Technologies, Inc. Other brand and product names are trademarks of their respective holders. Specifications, products, and/or product names are all subject to change without notice.
 Copyright 2007 Zhone Technologies, Inc. All rights reserved.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>